

Model						
Product Name	BND-MASHV399(A)AF-H	BND-MASHV399(A)AF-H2	BND-MASHV399(A)AF-H3	BND-MASHV399(A)AF-H4	BND-MASHV399(A)AF-H5	BND-MASHV399(A)AF-H6
Nominal Energy	3.99Kwh	7.98Kwh	11.97Kwh	15.96Kwh	19.95Kwh	23.94Kwh
Nominal Voltage	76.8Vdc	153.6Vdc	230.4Vdc	307.2Vdc	384Vdc	460.8Vdc
Voltage Range	69.6-87.6Vdc	39.2-175.2Vdc	208.8-262.8Vdc	278.4-350.4Vdc	348-438Vdc	417.6-525.6Vdc
Rated Capacity	52Ah					
Nominal Charge/Discharge Current	26A/26A					
Max.Charge/Discharge Current	52A/52A					
IP Rating of Enclosure	Ip20					
Operating Temperature	-10-50°C					
Storage Temperature	-10-35°C					
Cell type	LiFePO ₄					
Power display	LCD					
Communication interface	Rs485,CAN(Optional)					
Cycle Life	≥6000 Cycles(80%DOD)					
Master LCD Indicator	4LED(SOC:25%-SOC100%),2LED(working,alarming),LCD					
Installation	Floor standing					
Warranty Period	5 years					
Certification	UN38.3,CE					